

## DE-CIX CLOUD ROUTER TECHNICAL SERVICE DESCRIPTION

### I. GENERAL PROVISIONS

#### 1. Overview, scope of application

DE-CIX Cloud ROUTER enables, data transfer between network service providers and cloud service providers, e.g. in multi- or hybrid cloud setups, by establishing a Layer 3 Virtual Private Network (L3VPN).

This document contains the Technical Service Description (TSD) for the Cloud ROUTER product. This TSD is part of the DE-CIX contractual framework.

This TSD shall apply only to the Cloud ROUTER product. The Cloud ROUTER product may, however, be a prerequisite for other DE-CIX services. This document contains only technical specifications and documentation. Please consult the Cloud ROUTER Special Service Level Agreement (Special SLA) for service levels.

#### 2. Amendment

This document may be revised and amended at any time pursuant to the provisions of the DE-CIX Agreement.

#### 3. Product prerequisites

Cloud ROUTER can host various Layer 2 connections such as DirectCLOUD and VirtualPNI to create the desired network setup. The Cloud ROUTER product requires the following prerequisites for its normal operation:

- Either cloud environments at the enabled Cloud Service Providers between which the exchange and routing of traffic is desired.
- Or DE-CIX customer Accesses between which the exchange and routing of traffic is desired.
- Or a combination of cloud environments and DE-CIX Accesses.
- Cloud ROUTER service does not require customers to have a physical equipment or data center presence, and thus, DE-CIX Access is not mandatory.

#### **4. Applicable standards**

Customer's use of the DE-CIX network shall at all times conform to the relevant standards as laid out in [STD0001](https://www.rfc-editor.org/rfc/rfc2547.txt) (<https://www.rfc-editor.org/rfc/rfc2547.txt>) and associated Internet STD documents.

#### **II. DATA LINK-LAYER CONFIGURATION (ISO/OSI LAYER 2)**

For Layer 2 relevant documentation please refer to the underlying Technical Service Description of supplementary DE-CIX L2 services.

#### **III. NETWORK-LAYER CONFIGURATION (ISO/OSI LAYER 3)**

##### **1. Bandwidth**

Bandwidth of the Cloud ROUTER product must be explicitly configured. The Cloud ROUTER bandwidth must be dimensioned equal to or greater than the sum of all connections. Violation of this condition voids all Cloud ROUTER service warranties.

##### **2. MTU**

The maximum IP MTU size is 9000 byte.

##### **3. Prefixes per Cloud ROUTER instance**

The Cloud ROUTER has a routing table size limit of 4000 prefixes (IPv4). Any additional prefixes exceeding this limit will be discarded.

##### **4. ASN**

Any Cloud ROUTER instance needs to be assigned a 2-byte or 4-byte ASN (public or private). Validity of assignment will not be verified by DE-CIX.

##### **5. BGP**

###### **Protocol Specification**

Cloud router supports BGP in version 4 (RFC 4271)

Category	Feature	Status
Internet Protocol	IPv4 addressing	yes
	IPv6 addressing	Not yet supported
Connections	BFD	Optional (on/off), fix <ul style="list-style-type: none"> <li>• transmit/recieve interval = 300</li> <li>• multiplier = 3</li> </ul>
BGP	Password Authentication	Optional, configurable
	Route Filtering / Validation	Not supported
	Prefix Limits	4000 (IPv4) Action: BGP session shutdown, retry after 15 minutes
Restrictions	IPv4 restrictions	none
	ASN restrictions	none